

Self-Propelled Telescopic Boom Lifts

E600JP

Brand Model	JLG E600JP	Dimensional Data	
Power Source		Ground Clearance	0.3 m / 1 ft
Batteries	8 x 6V, 415 A-h	Machine Height	2.54 m / 8.3 ft
Electrical System	48 Volts DC	Machine Length	10.15 m / 33.3 ft
Performance		Machine Width	2.42 m / 7.9 ft
Drive Speed - Platform Lowered	4.80 km/h / 3 mph	Platform Dimension A	0.76 m / 2.5 ft
Gradeability - 2WD	30 %	Platform Dimension B	1.83 m / 6 ft
Gradeability - 4WD	45 %	Platform Height	18.39 m / 60.3 ft
Platform Capacity	230 kg / 507.1 lb	Tailswing	1.23 m / 4 ft
Swing	400 Degrees	Tire Size	36/14LL-22.5 Foam-filled Non-marking
Swing Type	Non-Continuous	Wheelbase	2.74 m / 9 ft
Turning Radius - Outside	4.64 m / 15.2 ft	Reach Specifications	
Jib - Range of articulation	145 Degrees	Working Height	20.39 m / 66.9 ft
General Specifications		Working Outreach	14.19 m / 46.6 ft
Capacity - Hydraulic Reservoir	60 L / 15.9 gal.	Horizontal Jib Rotation	180 Degrees
Machine Weight (CE & GOST)	7965 kg / 17559.8 lb	Horizontal Outreach	13.54 m / 44.4 ft
		Platform Height	18.39 m / 60.3 ft

