

Self-Propelled Telescopic Boom Lifts M600JP

Brand Model	JLG M600JP
Power Source	
Auxiliary Power	48 Volts DC
Batteries	8 x 6V 390 A/hr AGM
Capacity - Fuel Tank	50 L / 13.2 gal
Electrical System	48 Volts DC
Generator / Engine - Brand	Kubota
Performance	
Axle Oscillation	0.20 m / 0.7 ft
Drive Speed - Platform Lowered	4.80 km/h / 3 mph
Gradeability - 2WD	30 %
Gradeability - 4WD	30 %
Platform Capacity	230 kg / 507.1 lb
Swing	400 Degrees
Swing Type	Non-Continuous
Turning Radius - Outside	4.64 m / 15.2 ft
Jib - Range of articulation	145 Degrees

Dimensional Data	
Ground Clearance	0.3 m / 1 ft
Machine Height	2.54 m / 8.3 ft
Machine Length	10.15 m / 33.3 ft
Platform Dimension A	0.76 m / 2.5 ft
Platform Dimension B	1.83 m / 6 ft
Tailswing	1.23 m / 4 ft
Tire Size	36/14LL-22.5 Foam-filled/ Non-marking
Wheelbase	2.74 m / 9 ft
Reach Specifications	
Working Height	20.39 m / 66.9 ft
Working Outreach	14.19 m / 46.6 ft
Horizontal Jib Rotation	180 Degrees
Horizontal Outreach	13.54 m / 44.4 ft
General Specifications	
Capacity - Hydraulic Reservoir	80 L / 21.1 gal.
Machine Weight (CE & GOST)	7807 kg / 17211.5 lb
Maximum Ground Bearing Pressure	3.90 Kg/cm2

