

Telescopic Boom Lifts

SPT26

Brand Model	SANY SPT26(SPT88)
Power Source	
Driver X Steer	4WD X2WS
Capacity - Fuel Tank	160 L
Engine	55.4W/2600rpm/TD2.9 /DEUTZ/China Stage
	55.4W/2600rpm/V3307-TE5AB/ Kubota/China Stage
Performance	
Platform occupancy max. (Unrestricted/Restricted /Restricted)	2 Persons and tools
	2 Persons and tools
	3 Persons and tools
Tilt sensor activation	X-5°/Y-5°
Turning radius max. (inside/outside)	3.66m/6.68m
Gradeability	45%
Driver speed-stowed	0-6.0km/h
Driver speed-raised	0-0.8km/h

Dimensions Data	
Platform height max.	26.7 m
Working height max.	28.7 m
Horizontal outreach max.	20.3 m
A-length (stowed)	12.3 m
B-Width (stowed)	2.49 m
C-Height (stowed)	3.05 m
Platform dimension (LxW)	2.44X0.91 m
D-Ground clearance	0.41 m
E-Wheelbase	3.05 m
Lift capacity (Unrestricted /Restricted/Restricted)	300kg/400kg/480kg
Turntable tail swing	1.50 m
Jib rotation	+70°/-65°
Turntable rotation	360°Continuous
Platform rotation	180°
Weight	15,700 kg

